

## 3m mp8030 manual

---

**3M**

MP8030 Multimedia Projector  
Operator 's Guide

*MP8030 Appareil de projection multimédia Guide de l'opérateur*

*MP8030 Multimedia-Projektor Bedienerhandbuch*

*Portatil Multimedia MP8030 Manual del usuario*

*MP8030 Proiettore multimedia Manuale dell'operatore*

*MP8030 Multimedia-Projektor Instruktionsbok*

*MP8030 Multimedia Projector Gebruiksaanwijzing*



**File Name:** 3m mp8030 manual.pdf

**Size:** 3887 KB

**Type:** PDF, ePub, eBook

**Category:** Book

**Uploaded:** 6 May 2019, 18:33 PM

**Rating:** 4.6/5 from 732 votes.

**Status:** AVAILABLE

Last checked: 16 Minutes ago!

**In order to read or download 3m mp8030 manual ebook, you need to create a FREE account.**

[\*\*Download Now!\*\*](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

### Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with 3m mp8030 manual . To get started finding 3m mp8030 manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



## Book Descriptions:

### 3m mp8030 manual

The internal 3LCD technology is an innovative 3chip design that sets itself apart by delivering vibrant, truetolife images with better color brightness and a wider color gamut. This product has been produced in accordance with 3M's highest quality and safety standards to ensure smooth and troublefree use in the years to come. For optimum performance, please follow the operating instructions carefully. We hope you will enjoy using this high performance product in your meetings, presentations and training sessions. LIMITED WARRANTY 3M warrants this product against any defects iPay particular attention to areas where this. It may also be used to alert against unsafe practices. 2. Close supervision is necessary when any applianII or laptop computer connections. Carefully unpack and verify that you have all of the items shown below in Figure 11. If any of these items are missing, please contact your place of purchase.Switching your presentation from a computer to a video image back to a computer simply requires the push of a button on the remote control keypad or control panel keypad. The MP8030 Multimedia ProThe power cord Figure 33 is detachable from the projector and has different connection plugs on each end. Plug the female end into the power cord terminal on the projector and the male end into a properly grounded electrical outlet. Figure 33. Connecting the Power Cord Computer RGB Connection There are two input jacks and one The remote control VOLUME and MUTE buttons will control the external speaker volume levels. If you are giving a multimedia After the best projectortoscreen distance has been determined, the position of the projection screen in relation to the center of the projection lens must be considered.Push the lock lever to the lock position to secure each projector leg. UNLOCK LOCK Lock Lever Foot Figure 311. Projector Leg Adjustment Note Both projector legs must be raised or lowered the same amoRefer to Section 3 to make all cable connections.<http://www.ridendo.cz/files/combinatorics-a-guided-tour-solutions-manual.xml>

- **3m mp8030 manual, 3m mp8030 manual pdf, 3m mp8030 manual download, 3m mp8030 manual free, 3m mp8030 manual instructions.**

When the input cables and power cords are connected, turn on the power, adjust the size and focus of the projected image and begin your presentation. Power On Turn on the projector power, then turn on the power to your input sources. The projector power switch is located in the lower right corner of Press again to restore the sound. If you cannot make the image fill the screen, move the projector further back from the screen. Focus Press the FOCUS button to adjust the sharpness of the image. The following oThis arrow indicates that a submenu Figure 44 with additional options will display if you select that option.SECAM PATTERN Figure 44. Selecting VIDEO1 PThe 3MMultimedia Projector MP8030 has an automatic video selection function that will choose the correct video system or you can manually select the video system. If you select an input source that is not connected, the startup screen with an error message. Operator's Guide. MP8030 Appareil de projection multimedia Guide de l'opérateur. MP8030 MultimediaProjektor Bedienerhandbuch. Portatil Multimedia MP8030 Manual. Page 2 Table of Contents Table of ContentsWarranty..... Page 3 Table of Contents, continued. Section 6 Lamp Replacement..... Page 4 Warranty WarrantyThis product has been produced. Page 5 Safeguards SafeguardsPay particular attention to areas where thisThe 3MMultimedia Projector MP8030 is shipped with the necessary cables required. Page 7 Section 2 Product Description Section 2 Product DescriptionThe 3MMultimedia Projector MP8030 integrates metal halide lamp and polysilicon display technology. Page 8 Section 3 Setup Section 3 SetupIt only takes a few minutes to connect the 3MMultimedia Projector MP8030 to. Page 9 Power ConnectionInsert the left and right audio cable. Page 11 ProjectortoViewing Screen

Alignment. The size of the projection screen and the distance of the projector to the screen are important. Page 12 Adjusting the Projector

Elevation. <http://ruxthai-guesthouse-chiangmai.com/userfiles/combinatorics-a-problem-oriented-approach-solutions-manual.xml>

The elevation of the projected image can be adjusted by pushing the lock lever Figure 311. Page 13 Section 4 Operating the Projector Section 4 Operating the Projector Read the Important Safeguards before operating the 3M Multimedia Projector. Page 14 Mute Press the MUTE button to turn off the sound to the speakers. Press again to restore the sound. The projected image can be adjusted from onscreen menus using either the projector control panel or. Page 16 Some menu options will have an arrow at the end of the line VIDEO1, VIDEO2. This arrow indicates that a. Page 17 47. Input Menu The input source is selected from the Input menu. The 3M Multimedia Projector. Page 18 482. Changing the Screen Background Color Blank Button. The background color of the system menus can be white, blue or. If no input is detected when switching to an RGB or video source, either the. Page 20 493. Mouse Speed. Page 21 496. Auto Power Off. This function can be set to automatically switch the projector to standby mode if no input. Page 22 Section 5 Remote Control Section 5 Remote Control The remote control keypad Figure 51 has the. Page 23 Section 6 Lamp Replacement Section 6 Lamp Replacement If the projected image appears dark or the LAMP indicator. Page 24 Retaining Screws Use a standard screwdriver to Page 25 Section 7 Maintenance Section 7 Maintenance For best performance, keep your projector free of excess dust and surface dirt. Daily. Page 26 Insert the air cleaner in the door Figure 75, The 3M Multimedia Projector MP8030 has been designed to be as simple and troublefree to use. Page 28 Section 9 Technical Specifications Section 9 Technical Specifications The 3M Multimedia Projector MP8030 has the following physical dimensions The following illustration Figure 91 shows the terminal connections for the Dsub 15 pin. Page 31 We're easy to reach. The dealer has the option of repairing the product or returning it to 3M for repair or replacement. In the USA call 18003281371 for warranty or repair service.

SAVE THESE INSTRUCTIONS The information contained in this manual will help you operate and maintain your 3M Multimedia Projector MP8030 machine. Take a few minutes to review Section 2 to familiarize yourself with the MP8030 machine characteristics and then turn to Section 3 to set up the projector. Switching your presentation from a computer to a video image back to a computer simply requires the push of a button on the remote control keypad or control panel keypad. Desktop Computer CRT Display Laptop Computer Figure 31. Typical Cable Configuration. Find the cable that fits your computer type. The MP8030 comes with two computer input cables. The first cable Figure 34 fits IBM PC and compatible VGA video systems, and the other cable Figure 35 fits on the end of the first cable and adapts it to fit Apple MAC II computers and Apple MAC Powerbook laptop computers. Refer to section NO TAG Inverting the Image for more details. 33. Now What Your MP8030 is now connected and ready to power on. Turn to Section 4 for details on operating the projector. Downloaded From [projectormannual.com](http://projectormannual.com) 3M Manuals. Refer to Section 3 to make all cable connections. When the input cables and power cords are connected, turn on the power, adjust the size and focus of the projected image and begin your presentation. Highlighting a menu option will select that line. Downloaded From [projectormannual.com](http://projectormannual.com) 3M Manuals 3M 1996 3M Multimedia Projector MP8030. The 3M Multimedia Projector MP8030 has an automatic video selection function that will choose the correct video system or you can manually select the video system. The remote signal will bounce off of the projection screen and back to the sensor on the front of the 3M Multimedia Projector MP8030. Door Note The screw is a selfcontaining screw that cannot be removed from the cover. Screw Figure 61. Lamp Access Door Downloaded From [projectormannual.com](http://projectormannual.com) 3M Manuals 3M 1996 3M Multimedia Projector MP8030.

<http://www.drupalitalia.org/node/67928>

For best results, lamps should be replaced after 2000 hours. Downloaded From

projectormannual.com 3M Manuals 3M 1996 3M Multimedia Projector MP8030. Cleaning the Projection Lens Use 3M Overhead Cleaner 676 to remove surface dirt and smudges from the projection lens Figure 71. Figure 71. Cleaning the Lens Cleaning the Air Filter For best performance, clean the air filter every 10 hours of operations. If you should run into problems operating the projector, please review the troubleshooting information below. Problem Possible Solutions Power does not come on Power cord must be plugged into an electric outlet. Performance of individual units may vary by up to 10%. Downloaded From projectormannual.com 3M Manuals 3M 1996 3M Multimedia Projector MP8030. London, Ontario Mexico, D.F. 07000 95006 Cerge Pontoife Cedex 78697072466 Austin, TX 787269000. We do not guarantee We do not guarantee its accuracy and we do not make any claim of copyright. The copyright remains the property of their respective owners. The dealer has the option of repairing the product or returning it to 3M for repair or replacement. In the USA call 18003281371 for warranty or repair service. SAVE THESE INSTRUCTIONS The information contained in this manual will help you operate and maintain your 3M Multimedia Projector MP8030 machine. Switching your presentation from a computer to a video image back to a computer simply requires the push of a button on the remote control keypad or control panel keypad. Desktop Computer CRT Display Laptop Computer Figure 31. Typical Cable Configuration. The power cord Figure 33 is detachable from the projector and has different connection plugs on each end. Refer to section NO TAG Inverting the Image for more details. 33. Now What Your MP8030 is now connected and ready to power on. Turn to Section 4 for details on operating the projector. 3M 1996 3M Multimedia Projector MP8030. Refer to Section 3 to make all cable connections.

<http://eventoslanoria.com/images/canon-laser-class-9000-manual-pdf.pdf>

When the input cables and power cords are connected, turn on the power, adjust the size and focus of the projected image and begin your presentation. To return picture adjustments back to the factory settings, press the RESET button on the projector control panel or remote control transmitter 3M 1996 3M Multimedia Projector MP8030. Highlighting a menu option will select that line. 3M 1996 3M Multimedia Projector MP8030. The 3M Multimedia Projector MP8030 has an automatic video selection function that will choose the correct video system or you can manually select the video system. Bits Speed of mouse 7N1 mouse 7 databits, no parity, 1 stop bit movement.8 databits, no parity, 1 stop bit 3M 1996 3M Multimedia Projector MP8030. The remote signal will bounce off of the projection screen and back to the sensor on the front of the 3M Multimedia Projector MP8030. Door Note The screw is a selfcontaining screw that cannot be removed from the cover. Screw Figure 61. Lamp Access Door 3M 1996 3M Multimedia Projector MP8030. For best results, lamps should be replaced after 2000 hours. 3M 1996 3M Multimedia Projector MP8030. Cleaning the Projection Lens Use 3M Overhead Cleaner 676 to remove surface dirt and smudges from the projection lens Figure 71. Figure 71. Cleaning the Lens Cleaning the Air Filter For best performance, clean the air filter every 10 hours of operations. If you should run into problems operating the projector, please review the troubleshooting information below. Problem Possible Solutions Power does not come on Power cord must be plugged into an electric outlet. Performance of individual units may vary by up to 10%. 3M 1996 3M Multimedia Projector MP8030. Computer Projector Figure 93. RS232 Connector 3M 1996 3M Multimedia Projector MP8030. London, Ontario Mexico, D.F. 07000 95006 Cerge Pontoife Cedex 78697072466 Austin, TX 787269000. We do not guarantee its accuracy and we do not make any claim of copyright.

<https://extremeselfprotection.com/images/canon-laser-class-810-manual.pdf>

The copyright remains the property of their respective owners. Please check your inbox, and if you can't find it, check your spam folder to make sure it didnt end up there. Please also check your spam folder. This product has been produced in accordance with 3Ms highest quality and safety standards to ensure smooth and troublefree use in the years to come. We hope you will enjoy using this high

performance product in your meetings, presentations and training sessions. Proof of purchase date will be required with any warranty claim. In the event this product is found to be defective within the warranty period, 3M's only obligation and your exclusive remedy shall be replacement of any defective parts labor included. The dealer has the option of repairing the product or returning it to 3M for repair or replacement. In the USA call 18003281371 for warranty or repair service. This warranty gives you specific legal rights and you may have other rights which vary from state to state. It has been tested and found to comply with the limits for a Class A computing device pursuant to Subpart B of Part 15 of the FCC Rules, which are designed to provide reasonable protection against such interference when operated in a commercial environment. If normal coaxial cables are used, the cables must be enclosed in metal pipes or in a similar way to reduce the interference noise radiation. The outer shield must be connected to the ground. See Section 9. MAC II is a registered trademark of Apple Computer, Inc. All other products are trademarks or registered trademarks of their respective companies. Pay particular attention to areas where this symbol ! is shown. It may also be used to alert against unsafe practices. Do not leave appliance unattended while in use. The metal halide lamp produces a strong light which could damage your eyesight. Cords rated for less amperage than the appliance may overheat. Grasp plug and pull to disconnect. Loop cord loosely around appliance when storing.

Incorrect reassembly can cause electric shock when the appliance is subsequently used. Carefully unpack and verify that you have all of the items shown below in Figure 11. If any of these items are missing, please contact your place of purchase. Switching your presentation from a computer to a video image back to a computer simply requires the push of a button on the remote control keypad or control panel keypad. Connect your first input source to the Terminal 1 connectors and your second input source to the Terminal 2 connectors. Plug the female end into the power cord terminal on the projector and the male end into a properly grounded electrical outlet. Find the cable that fits your computer type. The MP8030 comes with two computer input cables. The first cable Figure 34 fits IBM PC and compatible VGA video systems, and the other cable Figure 35 fits on the end of the first cable and adapts it to fit Apple MAC II computers and Apple MAC Powerbook laptop computers. Connect the CRT cable into the RGBOut terminal to view the image on both the monitor and MP8030. The MP8030 will accept this signal through the SVIDEO1 or SVIDEO2 connectors. The SVHS cable has identical round fourpin connectors on either end Figure 36. Connect one end to the SVideo jack on the input source device, and the other end to the SVIDEO1 or SVIDEO2 terminal on the MP8030. Remember to connect the audio cables for sound output. Insert the left and right audio cable connectors Figure 37 to the input source, and connect the other end to the AUDIOL and AUDIOR terminals on the MP8030. The remote control VOLUME and MUTE buttons will control the external speaker volume levels. If you are giving a multimedia presentation that is complete with stereophonic sound, then you may want to consider connecting your audio source to a highquality stereo system. Of course, if you route your audio cables this way, the MP8030 audio controls VOLUME and MUTE will not function.

[www.vitrierbxl.be/wp-content/plugins/formcraft/file-upload/server/content/files/1626bdbbfff1017---concrete-design-manual-download.pdf](http://www.vitrierbxl.be/wp-content/plugins/formcraft/file-upload/server/content/files/1626bdbbfff1017---concrete-design-manual-download.pdf)

It is best to use a meeting room without wideopen windows. If there are light stripes from venetian blinds, try to find a viewing area that's away from them and remember, the light stripes will move as the hour changes. Refer to the table in Section 92 to determine how far away from the viewing screen you need to place the projector to fill the screen with the projected image. In other words, as the image grows larger, it also grows dimmer. For best results, experiment to find the right combination of projector to screen distance and room lighting. We're committed to dealing with such abuse according to the laws in your country of residence. When you submit a report, we'll investigate it and take the appropriate action. We'll get back to you only if we require additional details or have

more information to share. Note that email addresses and full names are not considered private information. Please mention this; Therefore, avoid filling in personal details. The manual is 0,59 mb in size. If you have not received an email, then probably have entered the wrong email address or your mailbox is too full. In addition, it may be that your ISP may have a maximum size for emails to receive. Check your email Please enter your email address. Very often issues with 3M MP8030 begin only after the warranty period ends and you may want to find how to repair it or just do some service work. Even oftener it is hard to remember what does each function in CRT Television 3M MP8030 is responsible for and what options to choose for expected result. Fortunately you can find all manuals for CRT Television on our side using links below. The lack of an instruction or false information given to customer shall constitute grounds to apply for a complaint because of nonconformity of goods with the contract. In accordance with the law, a customer can receive an instruction in nonpaper form; lately graphic and electronic forms of the manuals, as well as instructional videos have been majorly used.

A necessary precondition for this is the unmistakable, legible character of an instruction. Therefore, in an instruction of 3M MP8030 one could find a process description. An instructions purpose is to teach, to ease the startup and an items use or performance of certain activities. A good user manual introduces us to a number of additional functionalities of the purchased item, and also helps us to avoid the formation of most of the defects. An instruction contains a number of clues concerning respective functionalities, safety rules, maintenance methods what means should be used, eventual defects of 3M MP8030, and methods of problem resolution. Eventually, when one still cant find the answer to his problems, he will be directed to the 3M service. Lately animated manuals and instructional videos are quite popular among customers. These kinds of user manuals are effective; they assure that a customer will familiarize himself with the whole material, and wont skip complicated, technical information of 3M MP8030. After a successful purchase of an item one should find a moment and get to know with every part of an instruction. Currently the manuals are carefully prearranged and translated, so they could be fully understood by its users. The manuals will serve as an informational aid. Specs Ratio 2001 typical Time 35 milliseconds typical Scan 1538 kHz Scan 5684 Hz RCA jack RCA jack, 2 stereo mini pin jack Stereo mini pin jack Approvals FCC Part 15, Class A Oneyear limited warranty on parts and labor Projectors. The 3M projector has a brightness level of 500 ANSI lumens for crisp and colorful pictures to enjoy one's favorite movies, television shows, video games, sporting events, and more. The LCD projector features a 640x480 native resolution, a 43 native aspect ratio, and a 1001 contrast ratio. The projection image size of the 3M projector ranges from 40.0 inches to about 200.0 inches diagonally, which has a throw distance of 11.1 feet to 23.2 feet as well.

There is a single 3watt speaker located on the 3M MP 8030 to provide excellent sound production. The LCD projector takes a 260watt metal halide lamp, which produces an average of 2000 hours of lamp life for users to take advantage of. Verisign. Your transaction is secure. We cannot guarantee the accuracy of this data. The image to the right is for illustration purposes only the actual projector may look different. Please try again. MI Technologies, Inc. ShoppersAdda is the sole distributor of Lutema projector lamps in India. Please be aware that the warranty is not applicable if bought from other seller than ShoppersAdda. Please try your search again later. You can edit your question or post anyway. Economy Solution bulbs are manufactured in North America and provide the similar durability, quality and illustrative experience as your original one. Part Numbers MP8030 Amazon calculates a products star ratings based on a machine learned model instead of a raw data average. The model takes into account factors including the age of a rating, whether the ratings are from verified purchasers and factors that establish reviewer trustworthiness. If you want NextDay, we can save the other items for later. Order by, and we can deliver your NextDay items by. You won't get NextDay delivery on this order because your cart contains items that aren't "NextDay eligible". In your cart, save the other items for later in order to get NextDay delivery. Oops! There was a problem

with saving your items for later. You can go to cart and save for later there. They are safe, strong and reliable. Package Quantity 1 About This Item We aim to show you accurate product information. Manufacturers, See our disclaimer These Right Angle Power Cords feature a 90 degree C13 connector PC side which allows for better placement in tight situations. They are made to the same stringent standards as are standard PC power cables with the convenience of a right angle connector.

18AWG is a standard gauge cable and will work perfectly in most applications. These cables are designed to carry up to a 10 amp, 125 volt load. They are safe, strong and reliable. Ask a question Ask a question If you would like to share feedback with us about pricing, delivery or other customer service issues, please contact customer service directly. So if you find a current lower price from an online retailer on an identical, instock product, tell us and we'll match it. See more details at Online Price Match. All Rights Reserved. To ensure we are able to help you as best we can, please include your reference number Feedback Thank you for signing up. You will receive an email shortly at Here at Walmart.com, we are committed to protecting your privacy. Your email address will never be sold or distributed to a third party for any reason. For immediate help, please contact Customer Care. Thank you Your feedback helps us make Walmart shopping better for millions of customers. OK Thank you! Your feedback helps us make Walmart shopping better for millions of customers. Sorry. We're having technical issues, but we'll be back in a flash. Done. We delete comments that violate our policy, which we encourage you to read. Discussion threads can be closed at any time at our discretion. Posted in Projector Manuals Learn how your comment data is processed. Join the discussion on Facebook. All your questions, answered. The replacement lamp include generic housing compatible with 3M MP8030 Projector high quality compatible Projector Bulb The compatible bulb is made by the bulb manufacturer to meet the specifications and requirements for the 3M MP8030 Projector and to performs similar to the OEM bulb version. Offering high quality at an affordable price, these compatible bulbs are ideal substitutes for higher priced factory original bulbs.

Warranty The 3M MP8030 Projector replacement lamps are completely covered under our 90day warranty, which protects against any defective products. We are committed to offering an easy and safe Projector Lamp buying experience that brings peace of mind to all our customers. The replacement lamp include generic housing compatible with 3M MP8030 Projector high quality compatible Projector Bulb The compatible bulb is made by the bulb manufacturer to meet the specifications and requirements for the 3M MP8030 Projector and to performs similar to the OEM bulb version. Offering high quality at an affordable price, these compatible bulbs are ideal substitutes for higher priced factory original bulbs. Warranty The 3M MP8030 Projector replacement lamps are completely covered under our 90day warranty, which protects against any defective products. We are committed to offering an easy and safe Projector Lamp buying experience that brings peace of mind to all our customers. All prices USD. You must have JavaScript enabled in your browser to utilize the functionality of this website. Please consult your owners manual for information on resetting the lamp timer. Payment will be collected in US dollars. Local customs and duties will be charged by your local government at time of delivery. You may be contacted by customer service with an different freight charges for orders for oversized or heavier items. Please contact us at 800.867.2852 for more details. We will contact you with the charge prior to shipping your order. Each additional delivery will incur additional shipping charges. A Restocking Charge of 20% will apply to all items returned where Topbulb has made no error in merchandizing or shipping. Refunds will be made by original method of payment. All returns must arrive in its original packaging and all freight charges for the return of goods are to be paid by the customer. Topbulb may at any time limit the number of delivery attempts based on unfavorable delivery history.

This information is listed on our website within the Specifications section of each product if there is

a manufacturer's warranty. After 14 days, the customer is responsible for the shipping cost of warranty replacements. Please note a manufacturer's statement of Average Rated Life Hours does not imply a warranty. Please contact us if there is any obvious damage at the time of delivery. Please make all claims for replacement or credit within 14 days of delivery. They differ mainly in price, difficulty of replacement and reliability. Our offer is made up of original as well as compatible and hybrid projector lamps. Compatible projector lamps are manufactured by a different producer than the original manufacturer lamps; nevertheless, their quality and reliability is still decent. The major advantage of these lamps is their low price. We also sell bare bulbs without housing without the bulb mounting cage. Please take a look at our more detailed overview of lamp types in order to choose the best option. Shall I buy a module lamp or bare bulb. We offer 3M projector lamps both with module lamps and without the housing bare bulbs. When purchasing a bare bulb, you will use the lamp module already in your projector and will take the old bulb out and then will replace it with a new one. If you decide to buy a module lamp with housing, it can be replaced in just a few steps and thus is quite simple. For more information please take a look at our instructions for replacing a projector lamp. How can I save money when purchasing a projector lamp. When it comes to the importance of price, we offer several different projector lamp options. Projector lamps without housing represent the least expensive option. Another cheaper possibility is to buy lamps with compatible bulbs instead of original manufacturer lamps. Original module lamps in generic housing, as well as the alternatives from Diamond Lamps co. Which types of 3M projector lamps are reliable.

All projector lamps that we offer are highly reliable. However, in order to get the best quality, we recommend buying either original projector lamps both with and without housing or original projector lamps in generic housing or Diamond lamps. Which one should I choose We will help you find the right lamp. Angebote Hilfe Verkaufen Beobachtungsliste Beobachtungsliste einblenden Laden. Es ist ein Problem aufgetreten. The 3M projector has a brightness level of 500 ANSI lumens for crisp and colorful pictures to enjoy one's favorite movies, television shows, video games, sporting events, and more. The LCD projector features a 640x480 native resolution, a 43 native aspect ratio, and a 1001 contrast ratio. The projection image size of the 3M projector ranges from 40.0 inches to about 200.0 inches diagonally, which has a throw distance of 11.1 feet to 23.2 feet as well. There is a single 3watt speaker located on the 3M MP 8030 to provide excellent sound production. The LCD projector takes a 260watt metal halide lamp, which produces an average of 2000 hours of lamp life for users to take advantage of. Breiten 3M 9495 Klebeband für Handy LCD Display Reparatur Schulter Glas vers. NO HOURS 3M MP8635 Projector Beamer 3LCD SVGA 800 LUMENS EXCL REMOTE POWERS ON. Abbrechen Vielen Dank. Wir kümmern uns darum. Alle Rechte vorbehalten. Something went wrong. The 3M projector has a brightness level of 500 ANSI lumens for crisp and colorful pictures to enjoy one's favorite movies, television shows, video games, sporting events, and more. The LCD projector features a 640x480 native resolution, a 43 native aspect ratio, and a 1001 contrast ratio. The projection image size of the 3M projector ranges from 40.0 inches to about 200.0 inches diagonally, which has a throw distance of 11.1 feet to 23.2 feet as well. There is a single 3watt speaker located on the 3M MP 8030 to provide excellent sound production.

<http://www.drupalitalia.org/node/67930>